



B3F series... Our most comprehensive series of tactile switches includes 6 x 6 and 12 x 12 models with vertical and high-type forces, as well as radial taped types. All have positive click action and variations include horizontal and vertical, flat and projected types as well as versions with a high operating force and a long-life version, designed for 10,000,000 operations.

Dome Arrays... The B3DA dome arrays feature a dustproof construction and attach directly to the PCB so no soldering is required. The B3D, a single key type, is also available.

Positive click action... Omron's comprehensive range of tactile switches are suitable for keyboards with a membrane overlay or stand alone use with a keypad. These high quality switches provide a positive click action and are available with various forces of operation to suit most applications

Industry's smallest SMD Tactile Switch... Omron has introduced the industry's smallest tactile switches, in top and side actuating form. Both versions offer a sealed construction to ensure high reliability in dust-laden environments. The B3U switches have a footprint of just 3.0 x 2.5mm and are only 1.2mm high, enabling high-density mounting on printed circuit boards.



Omron Electronic Components Europe B.V.
Sales Division France
14, rue de Lisbonne
93561 Rosny Sous Bois
France
Tel: +33 1 56 63 19 00
Fax: +33 1 48 55 97 75

Omron Electronic Components Europe B.V.
Sales Division Central Europe
Gruber Strasse 60d
85586 Poing
Germany
Tel: +49 8121 77240
Fax: +49 8121 772440

Omron Electronic Components Europe B.V.
Sales Division Italy
Viale Certosa 49
20149 Milano
Italy
Tel: +39 02 3268 850
Fax: +39 02 3268 851

Omron Electronic Components Europe B.V.
Sales Division Benelux
Wegalaan 57
2132 JD Hoofddorp
The Netherlands
Tel: +31 23 568 1200
Fax: +31 23 568 1212

Omron Electronic Components Europe B.V.
Sales Division Iberia
Arturo Soria 95
28027 Madrid
Spain
Tel: +34 91 377 7900
Fax: +34 91 377 7987

Omron Electronic Components Europe B.V.
Sales Division Nordic
Box 1275
Norgegatan 1
S-164 32 Kista
Sweden
Tel: +46 8 632 3520
Fax: +46 8 632 3535

Omron Electronic Components Europe B.V.
Sales Division United Kingdom & Ireland
Building A, Campus Six, Caxton Way
Stevenage, Herts, SG1 2XD
United Kingdom
Tel: +44 870 750 5661
Fax: +44 870 750 5662

Omron Component Business B.V.
Emerging Markets Operations
CBC 1
Karadžičova 8
821 08 Bratislava
Slovakia
Tel: +421 2582 40950
Fax: +421 2582 40999

www.omroncomponents.com

Head Office
Omron Electronic Components Europe B.V.
Wegalaan 57
2132 JD Hoofddorp
The Netherlands
Tel: +31 23 568 1200
Fax: +31 23 568 1222

Ref. Y908-E2-04A



TACTILE SWITCHES

Selector Guide

BIG IDEAS
For a Small World

TACTILE SWITCH SELECTOR GUIDE



Model Number	B3F							B3W			B3FS	B3SL	B3SN	B3S	B3WN	B3J			B3U	B3DA	B3D															
Size	6 x 6mm	6 x 6mm	6 x 6mm	6 x 6mm	12 x 12mm	12 x 12mm	6 x 6mm	6 x 6mm	12 x 12mm	10 x 10mm	6 x 6mm	6x6mm	6 x 6mm	6 x 6mm	6 x 6mm	6 x 6mm	12 x 18mm	12 x 18mm	3.0 x 2.5mm	-	4mm diameter	5mm diameter														
Series	B3F-1000	B3F-1000-G	B3F-3000	B3F-3000G	B3F-4000/B3F-8000	B3F-5000	B3F-6000	B3W-1000	B3W-4000	B3W-9000	B3FS-1000	B3SL-1000	B3SN-1000	B3S-1000	B3WN-6000	B3J-1000	B3J-2000/3000/4000	B3J-5000/6000/7000	B3U	B3DA	B3D-4	B3D-5														
Features	Horizontal - Flat and projected	Horizontal - Flat - high reliability types	Vertical - Flat and projected	Vertical - flat - high reliability types	Horizontal - Flat and projected/ Flat and projected/ B3F-8000 with protective cover	Horizontal - Flat and projected - Long life expectancy and high reliability types	Horizontal - Flat and projected - radial taped type	Sealed construction that allows immersion cleaning after soldering. Dust-proof for applications in adverse conditions		Compact illumination with 1 or 2 LEDs	Surface mounting - ideal for high density mounting	Surface mounting sealed middle stroke switch	Surface mounting with sealed construction	Surface mounting for high-density packaging	Double-sealed construction ensures water-tight and dust-tight performance	Hinged tactile switch			Ultra small switch with high reliability contact	Dome arrays with dust-tight construction	Single-key type added to series of B3DA ultra-low profile dome array															
Contact	Silver-plated	Gold-plated	Silver-plated	Gold-plated	Silver-plated	Silver-plated	Gold-plated	Silver-plated	Silver-plated		Silver-plated	Silver-plated	Silver-plated	Silver-plated	Silver-plated	Silver-plated	Silver-plated	Silver-plated	Silver-plated	Silver-plated	Stainless steel	Stainless steel														
Operating Force	0.98N (100gf) 1.47N (150gf) 2.55N (260gf) 4.9N (500gf)	1.76N (180gf)	0.98N (100gf) 1.47N (150gf) 2.55N (260gf)	1.76N (180gf)	1.27N (130gf) 2.55N (260gf)	1.27N (130gf)	1.27N (130gf)	0.98N (100gf) 1.47N (150gf)	1.57N (160gf) 2.26N (230gf)	1.96N (200gf) 3.43N (350gf)	1.57N (160gf) 2.26N (230gf)	0.98N (100gf) 1.47N (150gf) 2.55N (260gf)	1.96N (200gf) 3.5N (357gf)	1.57N (160gf)	1.57N (160gf) 2.25N (230gf)	1.96N (200gf) 2.55N (260gf)	1.27N (130gf)	1.27N (130gf)	1.5N (top) 1.59N (side)	1.57N (160gf)	1.67N (170gf)	1.67N (170gf)														
Type	<ul style="list-style-type: none"> Flat Type (3.1mm height) - without ground Flat Type (3.1mm height) - with ground Flat type (4.3mm height - vertical model 3.15mm) - without ground Flat type (4.3mm height - vertical model 3.15mm) - with ground Flat type (5.0mm height - vertical model 3.85mm) - without ground Flat type (5.0mm height - vertical model 3.85mm) - with ground Flat type and others - without ground Flat type and others - with ground Projected type (7.3mm height - vertical model 6.15mm) - without ground Projected type (7.3mm height - vertical model 6.15mm) - with ground 1 LED without ground 2 LEDs without ground 																																			
Life Expectancy (operations)	1,000,000 (0.98N) 300,000 (1.47N) 100,000 (2.55N) 50,000 (4.9N)	300,000	1,000,000 (0.98N) 300,000 (1.47N) 100,000 (2.55N)	300,000	3,000,000 (1.27N) 1,000,000 (2.55N)	10,000,000	1,000,000 (1.96N) 300,000 (1.47N)	1,000,000 (1.57N) 300,000 (1.47N)	3,000,000 (1.96N) 1,000,000 (3.43N)	1,000,000 (1.57N) 200,000 (2.26N)	1,000,000 (0.98N) 300,000 (1.47N)	1,000,000 (1.57N) 100,000 (3.5N)	100,000	500,000 (1.57N) 300,000 (2.25N)	100,000	3,000,000	200,000 (top actuated) 100,000 (side actuated)	500,000 cycles (4mm diameter) 1,000,000 operations (5mm diameter)	500,000	1,000,000	500,000	1,000,000														
Ambient Operating Temperature	-25°C to 75°C							-25°C to 70°C			-25°C to 70°C		-25°C to 70°C		-25°C to 90°C		-25°C to 70°C			-25°C to 70°C		-25°C to 70°C		-40° to 80°C		-40° to 80°C										
Enclosure rating	IP00							IP00			IP00		IP64		IP64		IP64			IP00			IP40		IP00		IP00									
Cleaning	Not possible							Possible			Not possible		Not possible		-		Possible			Possible			Not possible		Not possible		Not possible									
Packaging	Box (standard)		1500		1500		1500		(200 for B3F-8000)		500		1,000 (radial)		1500		300		1500		2,000 (B3SL-1002P) 1,400 (B3SL01022P)		1500		1500		1000 (radial taped)		300		-		-		500 (20 sheets x 25 B3D)	
	Embossed tape (model number P: suffix)		-		-		-		-		-		-		-		-		-		-		-		-		-		-		-		-			
Key top for projected type	4 x 4mm		9 x 9mm		12 x 12mm		Diameter 6mm		Diameter 9.5mm		D-Shape																									